



RESE TERMICHE/HEAT OUTPUT - UNI EN 442 (deltaT 50K)

ART.

DIMENSIONI (mm.)

DIMENSIONS
DIMENSIONES
MÁBE
DIMENSIONES

RESE
OUTPUT
PUISSANCE
LEISTUNG
RENDIMIENTO

CAPACITA'
CAPACITY
CAPACITE'
INHALT
CONTENIDO

PESO
WEIGHT
POIDS
GEWICHT
PESO

RESE EL.
EL.OUTPUT
RENDEMENT EL.
EL.LEISTUNG
RENDIMIENTO EL.

	L	H	Z	Watt	Lt	Kg	Watt
CHA 770X450	450	770	425	493	2,9	8,0	400
CHA 770X500	500	770	475	539	3,3	8,8	400
CHA 770X550	550	770	525	581	3,7	9,5	400
CHA 770X600	600	770	575	622	4,1	10,3	400
CHA 770X750	750	770	725	749	5,2	12,5	700
CHA 770X1000	1000	770	975	961	7,1	16,2	700
CHA 1202X450	450	1202	425	739	4,5	12,1	700
CHA 1202X500	500	1202	475	771	5,1	13,3	700
CHA 1202X550	550	1202	525	810	5,7	14,2	700
CHA 1202X600	600	1202	575	866	6,3	15,5	700
CHA 1202X750	750	1202	725	1036	8,1	18,9	1000
CHA 1202X1000	1000	1202	975	1548	10,9	25,3	1000
CHA 1778X450	450	1778	425	1230	6,8	17,5	1000
CHA 1778X500	500	1778	475	1356	7,6	19,5	1000
CHA 1778X550	550	1778	525	1482	8,5	21,0	1000
CHA 1778X600	600	1778	575	1608	9,3	23,6	1000
CHA 1778X750	750	1778	725	1980	11,9	27,8	1000
CHA 1778X1000	1000	1778	975	2608	16,3	36,5	1000