



RESE TERMICHE/HEAT OUTPUT - UNI EN 442 (deltaT 50K)

ART.	DIMENSIONI (mm.)			RESA OUTPUT PUISSANCE LEISTUNG RENDIMIENTO	CAPACITA' CAPACITY CAPACITE' INHALT CONTENIDO	PESO WEIGHT POIDS GEWICHT PESO	RESA EL. EL.OUTPUT RENDEMENT EL. EL.LEISTUNG RENDIMIENTO EL.
	L	H	Z				
ELI 770X450	450	770	425	491	2,9	8,0	400
ELI 770X500	500	770	475	537	3,3	8,8	400
ELI 770X550	550	770	525	579	3,7	9,5	400
ELI 770X600	600	770	575	619	4,1	10,3	400
ELI 770X750	750	770	725	748	5,2	12,5	700
ELI 770X1000	1000	770	975	960	7,1	16,2	700
ELI 1202X450	450	1202	425	738	4,5	12,1	700
ELI 1202X500	500	1202	475	770	5,1	13,3	700
ELI 1202X550	550	1202	525	808	5,7	14,2	700
ELI 1202X600	600	1202	575	865	6,3	15,0	700
ELI 1202X750	750	1202	725	1035	8,1	18,9	1000
ELI 1202X1000	1000	1202	975	1547	10,9	25,3	1000
ELI 1778X450	450	1778	425	1229	6,8	17,5	1000
ELI 1778X500	500	1778	475	1355	7,6	19,5	1000
ELI 1778X550	550	1778	525	1481	8,5	21,0	1000
ELI 1778X600	600	1778	575	1607	9,3	23,6	1000
ELI 1778X750	750	1778	725	1979	11,9	27,8	1000
ELI 1778X1000	1000	1778	975	2607	16,3	36,5	1000