



RESE TERMICHE/HEAT OUTPUT - UNI EN 442 (deltaT 50K)

ART.

DIMENSIONI (mm.)

DIMENSIONS
DIMENSIONES
MÁBE
DIMENSIONES

RESA
OUTPUT
PUISSANCE
LEISTUNG
RENDIMIENTO

CAPACITA'
CAPACITY
CAPACITE'
INHALT
CONTENIDO

PESO
WEIGHT
POIDS
GEWICHT
PESO

RESA EL.
EL.OUTPUT
RENDEMENT EL.
EL.LEISTUNG
RENDIMIENTO EL.

	L	H	Z	Watt	Lt	Kg	Watt
PLA 792X45	450	792	424	414	2,0	7,5	400
PLA 792X50	500	792	474	448	2,3	8,0	400
PLA 792X55	550	792	524	479	2,6	14,5	400
PLA 792X60	600	792	574	512	2,9	14,0	500
PLA 792X75	750	792	724	605	3,6	14,0	500
PLA 792X100	1000	792	974	763	4,9	14,0	500
PLA 1216X45	450	1216	424	597	3,0	9,0	500
PLA 1216X50	500	1216	474	624	3,4	10,0	500
PLA 1216X55	550	1216	524	650	3,8	14,5	500
PLA 1216X60	600	1216	574	691	4,2	14,0	500
PLA 1216X75	750	1216	724	818	5,3	14,0	700
PLA 1216X100	1000	1216	974	1197	7,2	14,0	700
PLA 1799X45	450	1799	424	962	4,3	9,0	700
PLA 1799X50	500	1799	474	1056	4,8	10,0	700
PLA 1799X55	550	1799	524	1150	5,4	14,5	700
PLA 1799X60	600	1799	574	1243	5,9	14,0	700
PLA 1799X75	750	1799	724	1518	7,5	14,0	1000
PLA 1799X100	1000	1799	974	1994	10,2	14,0	1000